

User Guide

INF4305.0-Pinout





INF4305.0: DB9 to DB9 Cable (Male to Female)



Description:

Used for K-Series link cable. Connecting multiple K-Series CANin to CANout to link CAN bus and power. Can also be used to securely connect K-Series module to Kvaser CAN interfaces.


Tech Specs:

No of Pins	300mm
Gender	24 AWG 0.5 mm
Connector A	v
Temperature	9 pin D-Sub (DB9) plug [screw], pins compatible with CiA 303-1 (CAN and Power)
Type	Operating temperature: -20degC to +80degC
Weight	68 g
Colour	Black



CAN Connector

Female 9 pin standard D Type connector with screws




Pin No	Pin Function
Pin 2	CAN Low Signal
Pin 3	Ground
Pin 5	Power Ground
Pin 7	CAN High Signal
Pin 9	Power Supply 4.5 – 36 V



CAN Connector

Male 9 pin standard D Type connector with screws



Pin No	Pin Function
Pin 2	CAN Low Signal
Pin 3	Ground
Pin 5	Power Ground
Pin 7	CAN High Signal
Pin 9	Power Supply 4.5 – 36 V

Influx Technology Headquarters, UK

Office Suite 22,
Building 03 Millbrook Proving Ground,
Station Lane Millbrook
Bedford
MK45 2JQ

Telephone: +44 (0) 1525 842504
Sales: sales@influxtechnology.com

Influx Big Data Solutions Pvt Ltd, India

#2,
Krishvi,
Ground Floor,
Old Airport Road,
Domlur,
Bangalore,
560071

Phone: +91 7337748490
Sales: sales_india@influxtechnology.com

Influx Technology Asia, China

Rm.722,
Flr.7,
Lisheng Tower,
Wangfujing Street 201,
Dongcheng District,
Beijing,
100005,
China

Telephone: 86-10-5718-1640
Email: info@influxasia.com